

Applications

 Agriculture
 Construction and Demolition

 Landscaping
 Road work, Recycling and Cleaning

Main features

 Add versatility to your machine
 Easy to transport
 Uses Bob-Tach™ for quick and easy attachment changes


 Optional equipment includes rear stabilizers for increased performance and versatility
 Backhoes R30S and R35S are fitted with Klac D coupler as standard

Compatibility

Description	Item number	Compatible with loader
Backhoe R30S	6979700	A770-B, T450E IIIB, T590E IIIB, T590B iT4, T650E IIIB, T650E iT4, T650B iT4, T770E IV, T770E T3, T770B T3, T870E IV, T870B T3, S450E IIIA, S450B T2, S510E IIIA, S510B T2, S530E IIIA, S530B T2, S550E IIIB, S550B iT4, S570E IIIB, S570B iT4, S590E IIIB, S590B iT4, S630E IIIB, S630E iT4, S630B iT4, S650E IIIB, S650E iT4, S650B iT4, S770E IV, S770E T3, S770B T3, S850E IV, S850E T3, S850B T3, A770E IV
Backhoe R35S	7126559	A770-B, T650E IIIB, T650E iT4, T650B iT4, T770E IV, T770E T3, T770B T3, T870E IV, T870B T3, S630E IIIB, S630E iT4, S630B iT4, S650E IIIB, S650E iT4, S650B iT4, S770E IV, S770E T3, S770B T3, S850E IV, S850E T3, S850B T3, A770E IV

Characteristics and Performance

Description	Item number	Digging depth (mm)	Digging force with bucket (daN)	Digging force with dipper (daN)	Digging reach (mm)	Hook-up system
Backhoe R30S	6979700	2990.0	2140.0	1377.0	3757.0	Klac™
Backhoe R35S	7126559	3510.0	3130.0	2257.0	4272.0	Klac™

Weights and dimensions


Description	Item number	Operating weight (kg)	Shipping weight (kg)	Overall length (A) (mm)	Overall width (B) (mm)	Overall height (C) (mm)
Backhoe R30S	6979700	840.0	840.0	1317.0	1547.0	2087.0
Backhoe R35S	7126559	850.0	850.0	1317.0	1547.0	2535.0