

# DRIBBLE BARS

*Delivering Slurry Where It Is Needed*



**Low-Line**



**Swing Up**



**Combi**



**Duo Vertical Folding**



# LOW-LINE DRIBBLE BARS

Model Shown 9m Dribble Bar



7.5m Low Line Dribble Bar



9m Low Line Dribble Bar



12m Low Line Dribble Bar

Available for use all year round, and with any crops, SlurryKat dribble bars achieve a uniform spread of slurry/manure, with minimal plant contamination. As a result, fertiliser costs could be reduced by up to 80%.

Type	7.5m LL	9m LL	12m LL
Working Width (m)	7.5m	9m	12m
Transport Width (m)	2.3m	2.4m	2.4m
Transport Height**	1.6m	1.6m	1.7m
Standard Weight (Kgs)	689Kgs	790Kgs	986Kgs
Number of Elements	3	3	3
Shut Off with Valve	100%	100%	100%

Vogelsang Macerator	7.5m LL	9m LL	12m LL
Number of 40mm outlets	30	36	48
Number of 50mm outlets (optional)	30	36	48
Counter Blades	4	4	4

Linkage	7.5m LL	9m LL	12m LL
Linkage	3PT	3PT	3PT
Boom Folding	Hydraulic	Hydraulic	Hydraulic
Boom Teleshift	Manual	Manual	Hydraulic

Tractor Requirements	7.5m	9m LL	12m
Absorbed Average Power (HP)	90HP	95HP	110HP
Required Hydraulics	2DA + 1SA or ETS*	2DA + 1SA or ETS*	2DA + 1SA or ETS*

\* ETS - Eco-Matic Touch Screen (In cab control system)

\*\* Depending on mounting tractor

## Features

- 7.5-12m Working Width
- 2.4m Transport Width
- Horizontal Hydraulic Folding
- Connects with the Range of SlurryKat Reelers for Hose Reeling & Unreeling
- Vogelsang Exacut Distributor
- UV Resistant Slurry Delivery Hoses
- 360° Hose Swivel
- Fully Galvanised Construction
- Galvanised Finish
- Flow Meter Ready
- Boom Teleshift for Compact Transport



# SWING UP DRIBBLE BARS

Model Shown 12m c/w Sectional Boom Shut Off



12m Dribble Bar



15m Dribble Bar



24m Dribble Bar

In order to reduce transport sizes of our larger dribble bar models, SlurryKat has pioneered a unique Anti-Drip swing up system that not only makes the dribble bar very compact for transport, but also eliminates any problems with dripping of slurry/manure from the delivery hoses. This feature is available on our 12-24 metre models.

Type	12m	15m	24m
Working Width (m)	12m	15m	24m
Transport Width (m)	2.5m	2.5m	2.8m
Transport Height	3.4m	3.4m	3.6m
Standard Weight (Kgs)	1248Kgs	1474Kgs	2208Kgs
Number of Elements	3	3	3
Shut Off with Valve	50/50%	50/50%	50/50%

Vogelsang Macerator	12m	15m	24m
Number of 40mm outlets	48	60	96
Number of 50mm outlets	0	0	0
Counter Blades	8	8	8

Linkage	12m	15m	24m
Linkage	3/5PT	3/5PT	3/5PT
Boom Folding	Hydraulic	Hydraulic	Hydraulic

Tractor Requirements	12m	15m	24m
Absorbed Average Power (HP)	130HP	150HP	200HP
Required Hydraulics	4DA or ETS*	4DA or ETS*	40A or ETS*

\*ETS - Eco-Matic Touch Screen (In cab control system)

## Features

- 12m - 24m Working Width
- 2.5 - 2.7m Transport Width
- Hydraulic Folding
- Connects with the Range of SlurryKat Reelers for Hose Reeling & Unreeling
- Vogelsang Exacut Distributor
- UV Resistant Slurry Delivery Hoses
- 360° Hose Swivel
- Galvanised Finish
- Flow Meter Ready
- Hydraulic Boom Teleshift for Compact Transport



# DUO VERTICAL FOLDING DRIBBLE BARS

Model Shown 9m Dribble Bar  
c/w hydraulic teleshift



7.5m Dribble Bar



9m Dribble Bar



10.5m Dribble Bar

SlurryKat designed the Duo Dribble Bar with a dual purpose in mind. It can be mounted on the rear of any slurry tanker and then removed and used as the spreading device in the SlurryKat umbilical system.

Model	7.5m	9m	10.5m
Working Width (m)	7.5m	9m	10.5m
Transport Width (m)	2.3m	2.4m	2.4m
Transport Height (m)	3.6m	3.85m	4m
Standard Weight (Kgs)	692Kgs	738Kgs	898Kgs
Number of Elements	3	3	3
Shut Off Valve	100%	100%	100%

Vogelsang Macerator	7.5m	9m	10.5m
Number of 50mm Outlets	30	36	40
Counter Blades	4	4	4

Linkage	7.5m	9m	10.5m
Linkage	3pt	3pt	3pt
Boom Folding	Hydraulic	Hydraulic	Hydraulic

Tractor Requirements	7.5m	9m	10.5m
Absorbed Average Power (HP)	90HP	95HP	100HP
Required Hydraulics	2DA + 1SA or ETS*	2DA + 1SA or ETS*	2DA + 1SA or ETS*

\*DA = Double Acting Hydraulic Distributor  
ETS - Eco-Matic Touch Screen

## Features

- 7.5m - 10.5m Working Width
- 7.5 - 2.4m Transport Width
- Hydraulic Folding
- Connects with the Range of SlurryKat Reelers for Hose Reeling & Unreeling
- Vogelsang Exacut Distributor
- UV Resistant Slurry Delivery Hoses
- 360° Hose Swivel
- Galvanised Finish
- Flow Meter Ready
- Boom Teleshift for Compact Transport



# COMBI DRIBBLE BARS



SlurryKat Combi Dribble Bars represent a highly compact, lightweight and efficient means of umbilical slurry/manure spreading. The system combines up to 600m of layflat hose with a dribble bar and can be efficiently used by one operator.



## Features

- 7-9m Working Width
- 2.3m Transport Width
- Horizontal Hydraulic Folding
- Connects with the Combi Reeler for Hose Reeling, Unreeling and Spreading
- Vogelsang Exacut Distributor
- UV Resistant Slurry Delivery Hoses
- 360° Hose Swivel
- Fully Galvanised Construction
- Flow Meter Ready
- Boom Teleshift for Compact Transport

## Specification

Type	7.5m	9m
Working Width (m)	7.5m	9.0m
Transport Width (m)	2.3m	2.3m
Transport Height	2.1m	2.1m
Standard Weight (Kgs) Combi & Dribble Bar	790Kgs	870Kgs
Number of Elements	3	3
Shut Off with Valve	100%	100%

**COMPLEMENT YOUR SLURRYKAT DRIBBLE BAR WITH AN OROFLEX PIPELINE.**



**TALK TO A MEMBER OF OUR SALES TEAM TODAY.**



## DRIBBLE BARS OPTIONS

### Flowmeter System



### ETS - Eco-Matic Touch Screen (In Cab Control System)



*With Load Sensing Hydraulics  
(in cab touch screen)*

### Hydraulic Tele-shift on Booms



### Rear Work Lights



### EXTENDED WARRANTY PACKAGES ALSO AVAILABLE

*All our dribble bars are CE approved, come with a 3-year warranty\* as standard. So whether you are an independent farmer or a large scale contractor, SlurryKat has a system to meet your needs.*

*\*T&Cs Apply*

### For More Information:

#### HEAD OFFICE:

44 Lowtown Road, Waringstown, Craigavon, Co. Armagh, N. Ireland BT66 7SJ

**CALL:** + 44 (0) 28 3882 0862

**EMAIL:** [sales@slurrykat.com](mailto:sales@slurrykat.com)

**VISIT:** [www.slurrykat.com](http://www.slurrykat.com)

Your Local Distributor: