



The Infill Remover is the ultimate solution with regards to efficiently removing the infill from your pitch. In its raw form, the Infill Remover is similar to the Combinator. Therefore, you can easily change the working depth with the two spindles in the front of the machine, by means of the patented pendulum system. This patented system will automatically adjust both rollers, which assures an even operating result. When the machine is not operating, the elevator belt is positioned on top of the machine. However, before you start with the operation, you can easily unfold the belt to load the infill on a trailer or in a bag.



Do you want to remove SBR rubber from your artificial sport pitches? Does your pitch fail to meet the sport technical requirements? Or do you want to dispose your artificial pitch seperately? The Infill Remover is the ultimate solution, that will allow you to solve those issues.



The Infill Remover works with an unique brush. You have the possibility to adjust the stiffness of the brush. As a result it is possible to work on both new pitches, as well as on heavily compacted pitches. Depending on the characteristics of the pitch, it is possible to remove the entire layer of infill in jsut one operation.

THE WORKER IS KING



Туре	IR160		
Working width	160 cm / 63"		
Working depth	0 - 4 cm / 0-2"		
Dimensions operation (I x w x h)	160 x 400 x 180 cm / 63 x 157 x 71"		
Dimensions transport (l x w x h)	160 x 205 x 100 cm / 63 x 81 x 39"		
Weight	950 kg / 2100 lbs		
Power requirement	40 - 70 hp		
Linkage	Linkage Standard three-point hitch cat II		
Hydraulics	1x double acting hydraulic valve / transport unit (40 l/min)		
Hydraulics 1x double acting hydraulic valve / cylinder conveyor belt			