



Standard Low Loader 16 Tonne Gross



Standard Features

- Payload 12,000kg
- Rear Lights on Ramps
- Parking Brake
- Closed Beavertail
- Sprung Lowered Ramps – Angled Steel Slatted Design
- Fixed Shoe

Optional Features

- Sprung Drawbar
- Towing eye Type - Standard Ring, VBG, Ball, Rockinger etc,
- Towing Eye - Adjustable Height / Rotary / Adjustable & Rotary
- Axles - 8 Stud 80KPH (300 x 135)
- Axles - Full Commercial 10 Stud 105KPH (310 x 190)
- Wheels - 235/75 17.5 or 435/50 19.5
- Braking System – Air/Oil Options complete with Load Sensing Valve
- Fail Safe Valve
- Bale Wedge
- Hydraulic Ramps
- Hydraulic / Manual Jack Leg
- Tool Box – Front / Side
- Colour



Model—16 Tonne Gross	Low Loader - 20FT	Low Loader - 24FT
Permissible Total Weight	16,000kg	16,000kg
Carrying Capacity	12,900kg	12,500kg
Unladen Weight	3,100kg	3,500kg
Overall Length/Width/Height (mm)	8450 / 2500 / 2300	9440 / 2500 / 2300
Length of Flat Platform (mm)	4750	5750
Length of Beavertail (mm)	1620	1620
Ramp - Length / Width (mm)	1600 / 900	1600 / 900
Height of Platform (mm)	930	930
Floor	50mm Swedish Kiln Dried Soft Wood	50mm Swedish Kiln Dried Soft Wood
Wheel Track Width (mm)	1850	1850
No. of Axles	2 x 8 Stud	2 x 8 Stud
Axle Manufacturer	ADR/FAD	ADR/FAD
Axle Load	9000kg	9000kg
Maximum Hitch Load	3,500kg	3,500kg
Braking System	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking
Brake Size (mm)	300 x 90	300 x 90
Axle suspension	Hi-Roc 7 Leaf Springs	Hi-Roc 7 Leaf Springs
Tyre Dimensions	215/75 17.5 New J Rated	215/75 17.5 New J Rated
Maximum Speed	50 KPH	50 KPH
Drawbar Towing Eye	Heavy Duty 50mm Fixed Ring	Heavy Duty 50mm Fixed Ring

Contact

Herbst Machinery Ltd

120 Drumnakilly Road,
Omagh,
Co. Tyrone,
N. Ireland BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

General: info@herbst.co.uk

Sales: ashley@herbst.co.uk

Spare Parts: stores@herbst.co.uk