



For Earth, For Life
Kubota

GR

KUBOTA DIESEL RIDE-ON MOWER GR2120/GR2120S

A sleek and stylish ride-on mower loaded with professional features, the GR2120/GR2120S gives you first class results every time.

Introducing a revolutionary technology

GLIDE STEER



Performance

The brain and brawn to tackle the toughest tasks.

Glide Steer

This revolutionary technology enables the GR2120 to turn so sharply, it leaves only a 100 cm circle of uncut grass. Our unique Glide Steer feature makes cutting around trees, poles, and other narrow objects extremely efficient. Plus, because the inner rear wheel spins freely when turning, the grass is not damaged.

1 When driving in a straight direction, the GR2120 provides outstanding traction with its All-wheel drive, even on slopes.

2 For the sharpest turn possible, both the front wheels turn an incredible 70° at which point the inside rear wheel spins freely.

3 By spinning freely, the inside wheel does not damage the grass. Once the front wheels are straight, it resumes All-wheel drive.

Powerful Kubota engine

Tapping Kubota's legendary heritage of formidable engine designs, the GR2120 is equipped with a 15.6 kW, 3-cylinder diesel power plant. It generates a high torque rise that easily handles hours of heavy-duty mowing, even in long, wet grass, with a grass collector mounted.



Ultra-durable shaft drive

Unlike the belt-drive system utilised in gasoline mowers, our shaft-drive transmission, shaft-drive PTO, and hydraulic PTO clutch are incredibly durable and worry-free.



Easy to use, comfortable to operate and a pleasure to look at, the Kubota GR2120 is unrivalled for professional results.

Results, results, results. If that's what you're looking for there's no better choice than the GR2120. This high-end ride-on boasts our unique Glide Steer, an innovative Direct Chute System, a 15.6 kW engine, and a newly designed grass collector. Test drive the GR2120 today and experience unmatched performance in both efficiency and final finish.



Introducing a revolutionary technology

GLIDE STEER

Fatigue-reducing power steering

Feather-touch power steering enhances manoeuvrability, reduces fatigue, and makes operating the GR2120 possible for virtually anyone.



Versatile HST transmission

Kubota's reputable and versatile HST transmission is easily controlled by a single foot pedal and produces a maximum travel speed of 10km/h.



Suspension seat/full-flat deck

Oversized and generously padded, the GR2120's parallel linkage suspension seat can be adjusted to provide a high level of comfort to a wide range of operators. Its full-flat deck minimises operator fatigue by offering plenty of legroom.



Maintenance

The sophisticated grass collector design makes catching and dumping grass easy.

The grass collector on the GR2120 maintains a large capacity, yet, is lighter, easier to empty and utilises innovative mower technologies to prevent clogging.

Large capacity grass collector

The 450-litre grass collector has been made lower and longer to minimise clogging and reduce time between dumping. The collector also boasts lighter materials for easier handling.



Collector lever and lid

A gas-spring assist mechanism on the collector lever used for dumping makes lifting, even a full basket, easy. The lid of the collector opens wide, making maintenance easy work.



Well-designed duct

A handy electronic sensor is added to signal when the collector needs to be emptied. The wide duct leading from the mower deck is designed to move grass smoothly. A lever on the side of the tractor allows the operator to expel excess grass from the duct without leaving the tractor seat.



Turf

Our Direct Chute System ensures professional results.

The GR2120's Direct Chute System efficiently cuts and channels grass straight back into an integrated rear grass collector. The deck's cutting width is an ample 48 inches, and thanks to its centre-discharge configuration, you can execute tight, tree-hugging turns in either direction. For those who prefer a side-discharge mower, the GR2120S's mower deck is constructed of durable 10-gauge steel and is designed with a 5-inch deep shell. Whichever system you choose, you'll be assured professional and lasting results.



Side-discharge Mower



Easy reach cutting height adjustment dial



Deck cleaning pipe for connecting water hose



Hydraulic mower lift lever



Ultra-durable, long-life hexagonal belt



Rear Deflector

An optional rear deflector is available for times when you choose not to use the grass collector. This deflector discharges grass and dust directly onto the ground and easily attaches to the end of the duct, which leads from the mower deck.

Note: Some of the features shown may differ from those of the actual model.

Specifications

Model	GR2120		GR2120S
Engine	Kubota D782		
Model	Kubota D782		
Type	3 cylinder, diesel, water-cooled		
Total displacement	cm ³	778	
Engine gross power*	kW	15,6	
Maximum operating engine speed	min ⁻¹ (rpm)	3100 to 3250	
Engine layout	Horizontal		
Fuel tank capacity	ℓ	18	
Dimensions			
Overall length	mm	2880 (w/ GC)	2085
Overall width (w/ mower)	mm	1280	1550
Overall height (w/ ROPS up)	mm	2030	
Wheelbase	mm	1280	
Tread			
Front/Rear	mm	825/820	
Weight (w/ mower, GC, w/o fuel)	kg	545	470
Tyre size			
Front/Rear	16 × 7,5–8/23 × 10,50–12		
Transmission	Hydrostatic transmission		
Transmission drive	Shaft drive		
Speed control	Single foot pedal		
Front-wheel drive	Glide Steer		
Travelling speed			
Forward/Reverse	km/h	0–9,0/0–5,0	
Brake	Internal expanding brake		
PTO clutch	Hydraulic wet multi discs		
Mower deck drive	U-joint shaft		
Steering system	Glide Steer, fully hydraulic power steering		
Operator's deck	Flat		
Seat adjustment	Slide		
Seat suspension	Parallel linkage		
Fuel gauge	Std.		
Hour meter	Std.		
Easy checker	Std.		
Mower OPC.	Std.		
Travel OPC.	Std.		
Blade shut off brake	Built-in clutch		
Mower shut off when collector open	Std.		–
Grass collector			
Capacity	ℓ	450	–
Dumping system	Manual		–
Material of bag	Fabric / Steel		–
Optional accessories & implements	Cruise control, rear deflector		Cruise control, mulching kit
ROPS	Foldable		

Mower specifications

Cutting width	cm (in)	121.9 (48)	
Mower system	Direct chute		Side discharge
Mower blade drive	V. / hexagonal belt		V.
Lifting device	Hydraulic		
Mower mounting method	Quick attach		
Cutting height	mm	25–102	
Cutting height adjustment	Dial		
Cutting height position	11		
Number of blades	3		
Direction of rotation	2 clockwise viewed from operator, 1 counter clockwise		3 Clockwise viewed from operator
Minimum uncut diameter	m	1.0	
Mower deck ground clearance	mm	135	140

* Manufacturer's estimate

The company reserves the right to change the above specifications without notice.

Kubota

©2017 Kubota Corporation

KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
Phone (01844) 268000

www.kubota.co.uk



Kubota Genuine and Approved Parts

for maximum performance, durability and safety

