



DROP OUT HOSE REELERS

Carry multiple hose spools and easily drop off the empty spools



To unhitch the spool there is just one pin for the operator to remove after the tractor's linkage has been lowered to the ground.

The tractor can then be driven out of the spool and go on to collect the next free spool. No hydraulic hoses or complicated fixings have to be adjusted or removed when detaching or reattaching this system.

There is a standard specification reeler available with a galvanised spool on a

painted chassis available in three point linkage or A frame styles. The reel is powered by a protected heavy duty Danfoss hydraulic system.

Reels are available with 600m, 800m and 1000m capacities with divided or open section models made to the customers' requirements.

www.slurrykat.com



800m Sectional Reeler

800M Open Section Drop Out Reeler



- ▶▶ Easy attach umbilical hose reels
- ▶▶ Interchanged by unhooking one pin
- ▶▶ No hydraulic hoses or complicated fixings have to be adjusted or removed when detaching this reel.
- ▶▶ Bi-directional Danfoss hydraulic reel control
- ▶▶ Heavy duty gear to gear drive
- ▶▶ Divided or open section models made to the customers' requirements.
- ▶▶ Galvanised spool on a painted chassis available in 3 point or A-frame styles.
- ▶▶ Hi durable 2k paint finish unless otherwise stated

DROP OUT REELERS SPECIFICATION				Finish		Linkage			Tractor Requirements	
	Working Width	Transport Width	Sections	Chassis	Reel	3-Point	Heavy Duty A-Frame	Linkage	Required Hydraulics	Unladen Weight
600m (4" Hoses)	2.1m	2.1m	3x 200m	2k Paint Finish	Galvanised	Standard	Optional	Front	1DA+FR*	373 kgs
600m (up to 6" Hoses)	2.1m	2.1m	Single Open Random Wrap	2k Paint Finish	Galvanised	Standard	Optional	Front	1DA+FR*	390 kgs
800m (4" Hoses)	2.55m	2.55m	4x 200m	2k Paint Finish	Galvanised	Standard	Optional	Front	1DA+FR*	440 kgs
800m (up to 6" Hoses)	2.55m	2.55m	Single Open Random Wrap	2k Paint Finish	Galvanised	Standard	Optional	Front	1DA+FR*	460 kgs

*DA = Double Acting Hydraulic Distributor, FR = Free Return

Reels are available with 600m, 800m and 1000m capacities

**Head Office: 44 Loughton Road, Waringstown,
Craigavon, Co. Armagh, N. Ireland, BT66 7SJ**

TEL: +44 (0) 28 3882 0862 | 01179 866 163

Email: sales@slurrykat.com WEB: www.slurrykat.com



CE APPROVED: All SlurryKat equipment is CE approved. So whether you are an independent farmer or a large scale contractor, SlurryKat has a system to suit your needs