

>> Connected to you

C2 BLUE, C4 BLUE A2 TRANSPORTER, A4 TRANSPORTER STANDARDS RAISED

BRINNIAMES TRAILERS

UNITED KINGDOM





The Blue trailer range represents the essence of Brian James Trailers' core values. Those being quality you can depend on at competitive prices, Blue trailers offer real value for money.

C2 BLUE and **C4 BLUE** trailers are available in a wide range of sizes and configurations with either single or twin axles. Several models fit comfortably inside a standard garage, perfect if storage space is an issue.







C2 and C4 Blue

Innovation, value and quality.




• High grip punched ramps 1.90m long ramps store conveniently. Profiled guides allow the ramps to slide easily into the deck tray.

• Strong chassis design Durable galvanised chassis features a 'soft ride' suspension for superior performance, stability and comfort. 5 years chassis warranty is standard.



O Tie-down wheel 'sleeve' straps Approved by car manufacturers and race teams alike, these new straps hold the vehicle safely and securely without straining suspension geometry. Easy to fit, with multiple built-in tie-down points.

O Wheel chocks, Bolt in (pair) Fully adjustable wheel chocks bolt directly to the chassis bed.







O Storage bed locker (front) Lockable front storage locker, with automatic lift lid.

Internal size: 425mm length, 90mm depth, width dependent on load bed width.

O Deck slick pad For cars with soft 'slick' race tyres, pad raises tyre contact area above the punched deck.





O Alloy wheels C2 and C4 Blue are also available with new B2 style alloy wheels in standard Silver or diamond cut Anthracite (Anthracite shown).



- **O** Manual winch, 3 point adjustable pull positions, (illustrated above).
- O Manual winch, load pressure auto braked, 6 point adjustable pull positions.
- O Electric winch, powerful 12V, 4500lbs capacity with remote control lead (option not shown).

• Protected rear lighting Robust protection to rear lamp cluster.







The New Transporter range represents the ultimate evolution in trailer design. With a strong, durable galvanised chassis, low bed height and a range topping 3000kg gross capacity. Transporter trailers are perfectly suited for vehicle recovery, professional transport and motorsport alike.

Transporter trailers are available with load bed lengths from 2.70m to 5.00m, in single or twin axle variants. All feature internally stored 'easy glide' ramps and a flush fitting centre deck.



A4 TRANSPORTER

A2 and A4 Transporter

High specification as standard.



• Rear stands with foot pedal action Designed to compliment the 'easy glide' out ramps these spring loaded, foot operated support stands can be lowered or raised in seconds. Rear stands provide the dual function of load support when engaged and locking the ramps safely in position when towing.

O 2.40m punched ramps Additional length ramps available for low ground clearance vehicles. • Easy glide, high grip ramps 1.90m punched ramps pull out from the trailer bed in seconds. 'easy glide' rollers ensure the operation requires little effort.





O Wheel chocks, Professional Fully adjustable, quick release wheel chock system engages directly into the trailer chassis with in seconds.

O Tie-down wheel 'sleeve' straps Approved by car manufacturers and race teams alike, these new straps hold the vehicle safely and securely without straining suspension geometry. Easy to fit, with multiple built-in tie-down points.





O Manual winch, load pressure auto braked, + 6 point adjustable pull positions.


O Manual winch + 3 point adjustable pull positions.





O Fuel can storage Designed to carry either 1, 2 or 3 x 20 ltr Jerry cans. Lockable, twin opening doors. A2 and A4 transporters are available in Sargasso blue, Poppy red, Arcelor anthracite or Jet black body colour trim and the fuel storage locker can be colour matched to the trailer body.










• Storage bed locker (front) Lockable front storage locker, with automatic lift lid.

Internal size: 425mm length, 90mm depth, width dependent on chassis load bed width.




O Alloy wheels A2 and A4 Transporters are also available with new B2 style alloy wheels in standard Silver or diamond cut Anthracite (Anthracite shown).


A2 TRANSPORTER, A4 TRANSPORTER




Product code

C2 BLUE technical information.









| C2 BLUE – SINGLE AXLE | | | | | | | | | | | | | |
|----------------------------|----------|----------|----------|----------|----------|--|--|--|--|--|--|--|--|
| LOAD BED LENGTH m A | 2. | 70 | 3.20 | 3. | 70 | | | | | | | | |
| | | | | | | | | | | | | | |
| Gross kg | 1,300 | 1,500 | 1,500 | 1,500 | 1,500 | | | | | | | | |
| Load kg | 865 | 1,060 | 1,010 | 973 | 968 | | | | | | | | |
| DIMENSIONS | | | | | | | | | | | | | |
| Internal bed width m B | 1.80 | 1.80 | 1.80 | 1.80 | 2.00 | | | | | | | | |
| Overall trailer length m C | 4.18 | 4.18 | 4.68 | 5.18 | 5.18 | | | | | | | | |
| Overall trailer width m D | 2.18 | 2.18 | 2.18 | 2.18 | 2.38 | | | | | | | | |
| Bed load height m | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | | | | | | | | |
| RUNNING GEAR | | | | | | | | | | | | | |
| Wheel size | 12″ | 12″ | 12″ | 12" | 12" | | | | | | | | |
| Axles | 1 | 1 | 1 | 1 | 1 | | | | | | | | |
| Spare wheel | ٠ | ٠ | ٠ | • | • | | | | | | | | |
| Jockey wheel, side clamp | ٠ | ٠ | ٠ | • | • | | | | | | | | |
| RAMPS | | | | | | | | | | | | | |
| High grip, 1.90m E | ٠ | ٠ | ٠ | • | • | | | | | | | | |
| High grip, 2.40m E | — | - | 0 | 0 | 0 | | | | | | | | |
| WARRANTY | | | | | | | | | | | | | |
| 5 Year chassis warranty | ٠ | ٠ | ٠ | • | • | | | | | | | | |
| PRODUCTS | | | | | | | | | | | | | |
| Product code | 126-1010 | 126-1011 | 126-1111 | 126-1211 | 126-1221 | | | | | | | | |

| C4 BLUE – TWIN AXLE | | | | | | | | | | | | | |
|----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|--|--|
| LOAD BED LENGTH m A | 3. | 30 | 3.70 | | 4. | 00 | 4. | 5.00 | | | | | |
| CAPACITY | | | | | | | | | | | | | |
| Gross kg | 2,000 | 2,000 | 2,000 | 2,000 | 2,600 | 2,000 | 2,600 | 2,600 | 2,600 | 2,600 | | | |
| Load kg | 1,445 | 1,425 | 1,388 | 1,373 | 1,970 | 1,358 | 1,955 | 1,945 | 1,930 | 1,905 | | | |
| DIMENSIONS | | | | | | | | | | | | | |
| Internal bed width m B | 1.70 | 1.80 | 1.80 | 1.80 | 1.80 | 2.00 | 2.00 | 1.80 | 2.00 | 2.00 | | | |
| Overall trailer length m C | 4.62 | 4.62 | 5.18 | 5.48 | 5.48 | 5.48 | 5.48 | 5.98 | 5.98 | 6.48 | | | |
| Overall trailer width m D | 2.08 | 2.18 | 2.18 | 2.18 | 2.18 | 2.38 | 2.38 | 2.18 | 2.38 | 2.38 | | | |
| Bed load height m | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | | | |
| RUNNING GEAR | | | | | | | | | | | | | |
| Wheel size | 12" | 12″ | 12" | 12″ | 12″ | 12" | 12" | 12" | 12" | 12″ | | | |
| Axles | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | | | |
| Spare wheel | • | • | • | ٠ | • | • | • | • | • | • | | | |
| Jockey wheel, side clamp | • | • | • | ٠ | • | • | • | • | ٠ | • | | | |
| RAMPS | | | | | | | | | | | | | |
| High grip, 1.90m E | ٠ | • | ٠ | ٠ | ٠ | ٠ | ٠ | ٠ | ٠ | • | | | |
| High grip, 2.40m E | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | |
| WARRANTY | | | | | | | | | | | | | |
| 5 Year chassis warranty | • | • | ٠ | ٠ | • | ٠ | ٠ | • | ٠ | • | | | |
| PRODUCTS | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

126-2002 126-2012 126-2112 126-2212 126-2213 126-2222 126-2223 126-2313 126-2323 126-2423





2 TRANSPORTER

A2 TRANSPOR LOAD BED LENGTH m A

Internal bed width m B Overall trailer length m ${\bf C}$ Overall trailer width m D Bed load height m

High grip, glide out 1.90m E High grip, glide out 2.40m E


5 Year chassis warranty


Product code

Gross kg Load kg

Wheel size Axles Spare wheel Jockey wheel, HD


A2 TRANSPORTER technical information.







Δ

A4 TRANSPORTER technical information.



| RTER – SINGLE AXLE | | | | | A4 TRANSPORTER – TWIN AXLE | | | | | | | | | | | | |
|--------------------|---|--|---|---|--|---|---|--|---|--|---|---|--|---|--|---|---|
| 2.7 | 70 | 3.20 | .20 3.70 4.00 | | 00 | LOAD BED LENGTH m A | 3.30 | 3.70 | 4.00 | | | | 4.50 | | | 5.00 | |
| | | | | | CAPACITY | | | | | | | | | | | | |
| 1,300 | 1,500 | 1,500 | 1,500 | 1,500 | 1,500 | Gross kg | 2,000 | 2,000 | 2,000 | 2,600 | 2,000 | 2,600 | 2,600 | 2,600 | 3,000 | 2,600 | 3,000 |
| 865 | 1,060 | 1,010 | 973 | 965 | 955 | Load kg | 1,445 | 1,388 | 1,373 | 1,970 | 1,358 | 1,955 | 1,945 | 1,930 | 2,320 | 1,905 | 2,295 |
| | | | | | DIMENSIONS | | | | | | | | | | | | |
| 1.80 | 1.80 | 1.80 | 1.80 | 1.70 | 2.00 | Internal bed width m B | 1.70 | 1.80 | 1.80 | 1.80 | 2.00 | 2.00 | 1.80 | 2.00 | 2.00 | 2.00 | 2.00 |
| 4.24 | 4.24 | 4.74 | 5.24 | 5.38 | 5.54 | Overall trailer length m C | 4.68 | 5.24 | 5.54 | 5.54 | 5.54 | 5.54 | 6.04 | 6.04 | 6.04 | 6.54 | 6.54 |
| 2.18 | 2.18 | 2.18 | 2.18 | 2.08 | 2.38 | Overall trailer width m D | 2.08 | 2.18 | 2.18 | 2.18 | 2.38 | 2.38 | 2.18 | 2.38 | 2.38 | 2.38 | 2.38 |
| 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | Bed load height m | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 | 0.42 |
| | | | | | RUNNING GEAR | | | | | | | | | | | | |
| 12″ | 12" | 12″ | 12" | 12″ | 12″ | Wheel size | 12″ | 12" | 12″ | 12″ | 12" | 12″ | 12″ | 12″ | 12″ | 12″ | 12" |
| 1 | 1 | 1 | 1 | 1 | 1 | Axles | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| • | • | • | ٠ | • | • | Spare wheel | • | • | • | • | • | • | • | • | • | • | • |
| • | • | • | • | • | • | Jockey wheel, auto retract | • | • | • | • | • | • | ٠ | • | • | • | • |
| | | | | | RAMPS | | | | | | | | | | | | |
| • | • | • | ٠ | • | • | High grip, glide out 1.90m E | • | ٠ | • | • | • | • | • | • | • | • | • |
| - | - | 0 | 0 | 0 | 0 | High grip, glide out 2.40m E | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | | | | | | WARRANTY | | | | | | | | | | | |
| • | • | • | ٠ | • | • | 5 Year chassis warranty | • | ٠ | ٠ | • | • | • | ٠ | • | • | • | ٠ |
| | | | | | | PRODUCTS | | | | | | | | | | | |
| 125-1010 | 125-1011 | 125-1111 | 125-1211 | 125-1301 | 125-1312 | Product code | 125-2002 | 125-2112 | 125-2212 | 125-2213 | 125-2222 | 125-2223 | 125-2313 | 125-2323 | 125-2324 | 125-2423 | 125-2424 |
| | 2: 1,300 865 1.80 4.24 2.18 0.42 12" 1 • • • • • | 2.70 1,300 1,500 865 1,060 1.80 1.80 4.24 4.24 2.18 0.42 0.42 0.42 12" 12" 1 1 • • • • • • • • • • • • • • • • • • • • • • | 2.70 3.20 1,300 1,500 1,500 865 1,060 1,010 865 1,060 1,010 1.80 1.80 1.80 4.24 4.24 4.74 2.18 2.18 2.18 0.42 0.42 0.42 12" 12" 12" 1 1 1 • • • • • • • • • • • • • • • • • • • • • • • • • • • • • • | 2.70 3.20 3.70 1,300 1,500 1,500 1,500 865 1,060 1,010 973 1.80 1,80 1,80 973 1.80 1,80 1,80 973 1.80 1,80 1,80 973 1.80 1.80 1,80 973 1.80 1.80 1,80 1.80 4.24 4.24 4.74 5.24 2.18 2.18 2.18 2.18 0.42 0.42 0.42 0.42 12" 12" 12" 12" 1 1 1 1 • • • • • • • • • • • • • • • • • • • • • • • • • • • • • • <td>$\begin{array}{c c c c c c c c c c c c c c c c c c c$</td> <td>$\begin{array}{c c c c c c c c } \hline 3.20 & 3.70 & 4.00 \\ \hline 3.20 & 3.70 & 4.00 \\ \hline \\ \hline \\ 1,300 & 1,500 & 1,500 & 1,500 & 1,500 \\ \hline \\ 865 & 1,060 & 1,010 & 973 & 965 & 955 \\ \hline \\ 1.80 & 1.80 & 1.80 & 1.80 & 1.70 & 2.00 \\ \hline \\ 4.24 & 4.24 & 4.74 & 5.24 & 5.38 & 5.54 \\ \hline \\ 2.18 & 2.18 & 2.18 & 2.18 & 2.08 & 2.38 \\ \hline \\ 0.42 & 0.42 & 0.42 & 0.42 & 0.42 & 0.42 \\ \hline \\ \hline \\ 12'' & 12'' & 12'' & 12'' & 12'' & 12'' \\ \hline \\ 11 & 1 & 1 & 1 & 1 & 1 \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet \\ \bullet \\$</td> <td>2.70 3.20 3.70 4.00 LOAD BED LENGTH m A CAPACITY 1,300 1,500 1,500 1,500 1,500 Gross kg 865 1,060 1,010 973 965 955 Load kg DIMENSIONS 1.80 1.80 1.80 1.70 2.00 Internal bed width m B 4.24 4.24 4.74 5.24 5.38 5.54 Overall trailer length m C 2.18 2.18 2.18 2.08 2.38 Overall trailer width m D 0.42 0.42 0.42 0.42 0.42 Bed load height m 12" 12" 12" 12" Wheel size Bel load height m 12" 12" 12" 12" Wheel size Jockey wheel, auto retract 1 1 1 1 Akles Jockey wheel, auto retract 1 1 1 1 Akles Jockey wheel Jockey wheel 1 1 1</td> <td>2.70 3.20 3.70 4.00 LOAD BED LENGTH m A 3.30 CAPACITY 1,300 1,500 1,500 1,500 1,500 Gross kg 2,000 865 1,060 1,010 973 965 955 Load kg 1,445 1.80 1.80 1.80 1.70 2.00 Internal bed width m B 1.70 4.24 4.74 5.24 5.38 5.54 Overall trailer length m C 4.68 2.18 2.18 2.18 2.08 2.38 Overall trailer width m D 2.08 0.42 0.42 0.42 0.42 0.42 0.42 1.2" 12" 12" 12" 12" Wheel size 12" 1 1 1 1 Axles 2 • • • • • 9 • 1.80 1.80 1.80 1.70 2.08 2.38 0.42 0.42 0.42 0.42</td> <td>2.70 3.20 3.70 4.00 IOAD BED LENGTH m A 3.30 3.70 CAPACITY $1,300$ $1,500$ $1,500$ $1,500$ $1,500$ $0,500$ $0,000$ $2,000$ $2,000$ 865 $1,060$ $1,010$ 973 965 955 Load kg $1,445$ $1,388$ DIMENSIONS 1.80 1.80 1.80 1.70 2.00 Internal bed width m B 1.70 1.80 4.24 4.74 5.24 5.38 5.54 Overall trailer length m C 4.68 5.24 2.18 2.18 2.18 2.08 2.38 Overall trailer width m D 2.08 2.18 0.42 0.42</td> <td>2.70 3.20 3.70 4.0 LOAD BED LENGTH m A 3.30 3.70 CAPACITY $1,300$ $1,500$ $1,500$ $1,500$ $1,500$ 550 Gross kg $2,000$ $2,000$ $2,000$ 865 $1,060$ $1,010$ 973 965 955 Load kg $1,445$ $1,388$ $1,373$ DIMENSIONS 1.80 1.80 1.70 2.00 2.08 2.18 5.54 2.18 <td< td=""><td>2.70 3.70 4.00 LOAD BED LENGTH m A 3.30 3.70 4.00 CAPACITY 1,300 1,500 1,500 1,500 1,500 1,500 2,000 1,000 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00</td><td>2.70 3.20 3.70 4.00 IOAD BED LENGTH m A 3.30 3.70 4.00 1,300 1,510 1,51</td><td>2.703.203.704.00LOAD BED LENGTH m A3.303.703.704.00CAPACITY1.3001.5001.5001.5001.5001.5001.5001.5001.5002.0</td><td>2.70 3.20 3.70 4.00 LOAD BED LENGTH M A 3.30 3.70 4.00 4.00 CAPACITY 1.300 1.500 1.500 1.500 1.500 1.500 Gross kg 2.000 1.000 7.03 9.65 1.955 Load kg 1.445 1.388 1.30 1.80</td><td>2.703.203.704.00LOAD BED LENGTH m A3.303.704.004.004.50CAPACITY1.3001.5001.5001.5001.5001.5001.5001.500Gross kg2.0002</td><td>2.7.0 3.20 3.70 4.00 IOAD BED LENGTH M A 3.30 3.70 4.00 4.00 4.50 CAPACITY 1.300 1.500 2.000 2.000 2.000 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 1.500 1.500 2.200 1.500 1.500 2.200 1.500 1.500 2.200 1.50 1.50 2.200 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00</td><td>1 3.20 3.70 4.00 1.000 BED LENGTH m A 3.30 3.70 4.00 4.50 5.00 5.00 1.300 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 Gross kg 2.000 1.000 9.00 2.000 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.00 1.00 9.00 2.00 1.00 9.00 2.00 1.00 1.00 1.00 9.00 9.00 9.00 2.00</td></td<></td> | $\begin{array}{c c c c c c c c c c c c c c c c c c c $ | $\begin{array}{c c c c c c c c } \hline 3.20 & 3.70 & 4.00 \\ \hline 3.20 & 3.70 & 4.00 \\ \hline \\ \hline \\ 1,300 & 1,500 & 1,500 & 1,500 & 1,500 \\ \hline \\ 865 & 1,060 & 1,010 & 973 & 965 & 955 \\ \hline \\ 1.80 & 1.80 & 1.80 & 1.80 & 1.70 & 2.00 \\ \hline \\ 4.24 & 4.24 & 4.74 & 5.24 & 5.38 & 5.54 \\ \hline \\ 2.18 & 2.18 & 2.18 & 2.18 & 2.08 & 2.38 \\ \hline \\ 0.42 & 0.42 & 0.42 & 0.42 & 0.42 & 0.42 \\ \hline \\ \hline \\ 12'' & 12'' & 12'' & 12'' & 12'' & 12'' \\ \hline \\ 11 & 1 & 1 & 1 & 1 & 1 \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet & \bullet \\ \hline \\ \bullet & \bullet & \bullet \\ \bullet \\$ | 2.70 3.20 3.70 4.00 LOAD BED LENGTH m A CAPACITY 1,300 1,500 1,500 1,500 1,500 Gross kg 865 1,060 1,010 973 965 955 Load kg DIMENSIONS 1.80 1.80 1.80 1.70 2.00 Internal bed width m B 4.24 4.24 4.74 5.24 5.38 5.54 Overall trailer length m C 2.18 2.18 2.18 2.08 2.38 Overall trailer width m D 0.42 0.42 0.42 0.42 0.42 Bed load height m 12" 12" 12" 12" Wheel size Bel load height m 12" 12" 12" 12" Wheel size Jockey wheel, auto retract 1 1 1 1 Akles Jockey wheel, auto retract 1 1 1 1 Akles Jockey wheel Jockey wheel 1 1 1 | 2.70 3.20 3.70 4.00 LOAD BED LENGTH m A 3.30 CAPACITY 1,300 1,500 1,500 1,500 1,500 Gross kg 2,000 865 1,060 1,010 973 965 955 Load kg 1,445 1.80 1.80 1.80 1.70 2.00 Internal bed width m B 1.70 4.24 4.74 5.24 5.38 5.54 Overall trailer length m C 4.68 2.18 2.18 2.18 2.08 2.38 Overall trailer width m D 2.08 0.42 0.42 0.42 0.42 0.42 0.42 1.2" 12" 12" 12" 12" Wheel size 12" 1 1 1 1 Axles 2 • • • • • 9 • 1.80 1.80 1.80 1.70 2.08 2.38 0.42 0.42 0.42 0.42 | 2.70 3.20 3.70 4.00 IOAD BED LENGTH m A 3.30 3.70 CAPACITY $1,300$ $1,500$ $1,500$ $1,500$ $1,500$ $0,500$ $0,000$ $2,000$ $2,000$ 865 $1,060$ $1,010$ 973 965 955 Load kg $1,445$ $1,388$ DIMENSIONS 1.80 1.80 1.80 1.70 2.00 Internal bed width m B 1.70 1.80 4.24 4.74 5.24 5.38 5.54 Overall trailer length m C 4.68 5.24 2.18 2.18 2.18 2.08 2.38 Overall trailer width m D 2.08 2.18 0.42 | 2.70 3.20 3.70 4.0 LOAD BED LENGTH m A 3.30 3.70 CAPACITY $1,300$ $1,500$ $1,500$ $1,500$ $1,500$ 550 Gross kg $2,000$ $2,000$ $2,000$ 865 $1,060$ $1,010$ 973 965 955 Load kg $1,445$ $1,388$ $1,373$ DIMENSIONS 1.80 1.80 1.70 2.00 2.08 2.18 5.54 2.18 <td< td=""><td>2.70 3.70 4.00 LOAD BED LENGTH m A 3.30 3.70 4.00 CAPACITY 1,300 1,500 1,500 1,500 1,500 1,500 2,000 1,000 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00</td><td>2.70 3.20 3.70 4.00 IOAD BED LENGTH m A 3.30 3.70 4.00 1,300 1,510 1,51</td><td>2.703.203.704.00LOAD BED LENGTH m A3.303.703.704.00CAPACITY1.3001.5001.5001.5001.5001.5001.5001.5001.5002.0</td><td>2.70 3.20 3.70 4.00 LOAD BED LENGTH M A 3.30 3.70 4.00 4.00 CAPACITY 1.300 1.500 1.500 1.500 1.500 1.500 Gross kg 2.000 1.000 7.03 9.65 1.955 Load kg 1.445 1.388 1.30 1.80</td><td>2.703.203.704.00LOAD BED LENGTH m A3.303.704.004.004.50CAPACITY1.3001.5001.5001.5001.5001.5001.5001.500Gross kg2.0002</td><td>2.7.0 3.20 3.70 4.00 IOAD BED LENGTH M A 3.30 3.70 4.00 4.00 4.50 CAPACITY 1.300 1.500 2.000 2.000 2.000 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 1.500 1.500 2.200 1.500 1.500 2.200 1.500 1.500 2.200 1.50 1.50 2.200 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00</td><td>1 3.20 3.70 4.00 1.000 BED LENGTH m A 3.30 3.70 4.00 4.50 5.00 5.00 1.300 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 Gross kg 2.000 1.000 9.00 2.000 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.00 1.00 9.00 2.00 1.00 9.00 2.00 1.00 1.00 1.00 9.00 9.00 9.00 2.00</td></td<> | 2.70 3.70 4.00 LOAD BED LENGTH m A 3.30 3.70 4.00 CAPACITY 1,300 1,500 1,500 1,500 1,500 1,500 2,000 1,000 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00 | 2.70 3.20 3.70 4.00 IOAD BED LENGTH m A 3.30 3.70 4.00 1,300 1,510 1,51 | 2.703.203.704.00LOAD BED LENGTH m A3.303.703.704.00CAPACITY1.3001.5001.5001.5001.5001.5001.5001.5001.5002.0 | 2.70 3.20 3.70 4.00 LOAD BED LENGTH M A 3.30 3.70 4.00 4.00 CAPACITY 1.300 1.500 1.500 1.500 1.500 1.500 Gross kg 2.000 1.000 7.03 9.65 1.955 Load kg 1.445 1.388 1.30 1.80 | 2.703.203.704.00LOAD BED LENGTH m A3.303.704.004.004.50CAPACITY1.3001.5001.5001.5001.5001.5001.5001.500Gross kg2.0002 | 2.7.0 3.20 3.70 4.00 IOAD BED LENGTH M A 3.30 3.70 4.00 4.00 4.50 CAPACITY 1.300 1.500 2.000 2.000 2.000 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 2.600 1.500 1.500 2.200 1.500 1.500 2.200 1.500 1.500 2.200 1.50 1.50 2.200 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 2.00 | 1 3.20 3.70 4.00 1.000 BED LENGTH m A 3.30 3.70 4.00 4.50 5.00 5.00 1.300 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 1.500 Gross kg 2.000 1.000 9.00 2.000 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.000 1.000 9.00 2.00 1.00 9.00 2.00 1.00 9.00 2.00 1.00 1.00 1.00 9.00 9.00 9.00 2.00 |





BRIAN JAMES TRAILERS

>> Connected to you

NOTES

Specifications are subject to change without notice. Illustrations and photography may depict optional equipment.

www.brianjames.co.uk

© BRIAN JAMES TRAILERS LIMITED

Edition: 2019Q1_BLTR_UK_V2

Brian James Trailers Limited. Sopwith Way, Drayton Fields Industrial Estate Daventry, Northampton, NN11 8PB

T + 44 (0)1327 308 833

Brian James Trailers are available by contacting our sales team as well as through an extensive network of official dealers throughout the country.

For more information please call or visit our website.

www.brianjames.co.uk

Dealer information.

