

Slurry Pumps



Powerflo pumps

For standard reception pits.

Fixed depth 540 rpm PTO various depths from 4ft 6" to 15ft. 60 hp required.

For standard pits with extra performance required. Fixed depth 1000 rpm PTO various depths from 4ft 6" to 15ft. 120 hp required.

For slatted tanks.

Variable depth 540 rpm PTO. 70 hp required 6-8ft and 8-10ft.

For various slatted tanks.

Variable depth 1000 rpm PTO. 120 hp required 6-8ft and 8-10 ft.

Power Flow: FIXED DEPTH Various models to suit differing pit depths. 540 rpm

(50kW) or 1000 rpm (85 kW) at the PTO.

VARIABLE DEPTH Variable depth pumps which are easily transportable.

Ideal for slatted tanks. 540 rpm or 1000 rpm at the PTO.


Minimum hole size 510mm x 760mm.



Powerflo variable depth pump, 8-10ft.



External fins break lumps and force feed the impellor for high outputs.





All machines manufactured from high quality heavy duty steel, all with a fully galvanised finish, bottom bearing lubricated by the slurry, gearbox protection, aggressive cutting and chopping actions and high outputs and pressures achieved.



Slurry Mixers



Lagoon Mixer	15ft 17ft 20ft 24ft 29ft	For small to medium lagoons under 8' deep For medium lagoons For medium to large lagoons over 8' deep For large lagoons For large lagoons
Underslat mixer	9ft	For underground tanks with restricted access
Wallmixers		For regular mixing of above ground slurry stores
Storemaster mixer	12ft 16ft 20ft	Various vertical heights, all with a 20ft boom for mixing above ground slurry stores

All machines manufactured from high quality heavy duty steel, all with a fully galvanised finish, hydraulic depth adjustment, bottom bearing lubricated by the slurry and a long, problem-free life.



Dereham Road, Beeston, King's Lynn, Norfolk PE32 2LE Tel 01328 701992

Fax 01328 700111

Email enquiries@greencrop.co.uk

www.greencrop.co.uk

Dealer stamp